

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H02K 11/00, 3/00		A1	(11) International Publication Number: WO 00/57540 (43) International Publication Date: 28 September 2000 (28.09.00)
(21) International Application Number: PCT/EP00/02669 (22) International Filing Date: 23 March 2000 (23.03.00) (30) Priority Data: 60/125,857 24 March 1999 (24.03.99) US (71) Applicant (for all designated States except CA US): SHELL INTERNATIONALE RESEARCH MAATSCHAPPI B.V. [NL/NL]; Carel Van Bylandtlaan 30, NL-2596 HR The Hague (NL). (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400-4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA). (72) Inventor; and (75) Inventor/Applicant (for US only): SMITH, David, Randolph [US/NL]; Volmerlaan 8, NL-2288 GD Rijswijk (NL).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: MONITORING INTERNAL PARAMETERS OF ELECTRICAL MOTOR SYSTEMS

(57) Abstract

A process and system for measuring and monitoring data, such as temperature and vibrations, in an electrical motor comprises a fibre optical cable (5) embedded in the electrical insulation (4) of at least one wire (3) of the motor windings which cable thus forms an elongate thermometer and/or vibration sensor.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

MONITORING INTERNAL PARAMETERS
OF ELECTRICAL MOTOR SYSTEMS

Description Of Invention

This invention relates to an improved process and system to measure and monitor conditions of electrical submersible motors. The method and system according to the invention thereto employ optic fibers, sensors, and/or micromachines wound integrally with the electrical wire used in the construction of an electrical motor's stator or armature.

One embodiment of the invention wraps optic fiber and sensors familiar to those in the art of telemetry, around the electrical wire, and then encapsulates and attaches the optic fiber to the wire by covering or coating the electrical wire and the optic fiber with an insulation material. Hence the optic fiber and the sensors, machines, and devices are wound longitudinally along the length of the electric wire, and the two are then wound through the electric motor stator slots to form the stator windings. The stator can then have insulation applied to it and the electric wires through varnishing, epoxy coating, or any of the other insulation techniques used by those familiar to the art of making motors. Moreover, the invention allows for the curing temperature of said insulation materials to be closely monitored by using the optic fibers as an intrinsic temperature monitor by using optical time domain reflectometry techniques and Raman backscattering.

Another embodiment places the optic fiber and the associated devices for monitoring in a tube, and the tube is wound in the stator of the electrical motor with the electrical wire.

Another embodiment uses the optic fiber, wound around electrical wire and passed through the stator, to be a communication path between sensors out side of the electric motor.

5 This invention solves the problem of monitoring internal electrical motor parameters. For example it is often useful from both a design and development prospective as well for operational control, safety, and extending motor life, to monitor certain internal
10 parameters of an electric motor. This invention also allows parameters to be measured along multiple nodes along the axis of the motor as well as at different radial positions in the motor. These variables give useful insight to heat rise, heat flux, hot spots, and
15 the subsequent heat profiles in different motor designs, as well as offering an intimate knowledge of the motors internal conditions of pressure and vibration, and stator movement under during actual running and operation of the electrical system.

20 Electrical motor performance and life cycle are functions of these internal conditions, which the invention monitors. Therefore, this invention's ability to monitor these conditions in electrical motors allows for improvements and or changes in design and operations
25 to be made and then confirmed via the internal monitoring offered by this invention.

30 The most direct application of this technology is in the development of new, highly reliable, and more efficient electrical motors for subterranean oil and gas wells.

35 This invention will be used to design electrical motors that will have the internal parameters measured for many applications. It is often very useful to monitor the internal vibration of an electrical motor in operations to detect poor dampening in the system, poor

alignment of the motor rotor, or vibrations induced by start ups or implements and devices attached to the motors (i.e. compressors, fans, pumps, etc.). This will assist in designing more efficient and reliable electrical motors systems both from a mechanical perspective as well as an electrical perspective. This invention also provides a method to pass optical communications through an electrical motor from outside the electrical motor.

Description of a preferred embodiment

The invention will be described in more detail with reference to the accompanying drawings in which

Fig. 1 is a schematic cross-sectional view of an electrical motor having a stator with electrical wires of which at least one wire is equipped with a fibre optical sensor system embedded in the insulation;

Fig. 2 shows at a larger scale than Fig. 1 a cross-sectional view of the wire with fibre optical sensor system of Fig. 1; and

Fig. 3 shows at a larger scale than Fig. 1 a longitudinal sectional view of the wire and fibre optical sensor system of Fig. 1.

Referring to Fig. 1 there is shown an electrical motor having a rotor represented by arrow 1 and a stator 2 which comprises a series of electrical wires 3 that are wound such that when an electrical current passes through the wires 3 a rotating electromagnetic field is created which induces the rotor 1 to rotate relative to the stator 2. As shown in Fig. 2 and 3 at least one wire 3 has an electrical insulation coating 4 in which a fibre optical cable 5 is embedded, which cable 5 may be provided with suitable microsensors 6, such as an accelerometer to detect vibrations, and/or optic gratings, such as fibre bragg gratings 7 that reflect light of a wavelength equal to the grating width

and allow light of other wavelengths to pass through the cable 7. The gratings 7 may be designed such that the reflected wavelength varies with temperature such that the fibre optical cable 5 forms an elongate string of
5 miniature thermometers along the length of the wire 3. Likewise the optic sensors 6 may be formed by seismic sensors which are formed by similar gratings that reflect varying wavelengths in response to vibrations so that the fibre optical cable 5 is an elongate multiparameter
10 sensor system that accurately detects any overheating and/or vibrations, for example when the associated pump is blocked or runs dry or when a bearing has worn out.

C L A I M S

1. A process for measuring and monitoring electrical motor systems, said process comprising:

providing a motor system having at least one component selected from a stator and an armature, said at least one component connected to at least one electrical wire;

incorporating at least one means for data measurement with said at least one electrical wire;

collecting data with said at least one means for data measurement; and

transferring said collected data to a data collection station.

2. A process according to claim 1 wherein said means for collecting data is wrapped around said electrical wire.

3. A process according to claim 2 wherein said means for collecting data is encapsulated and attached to said electrical wire by covering or coating the electrical wire and the means for collecting data with an insulation material.

4. A process according to claim 1 wherein said means for collecting data is selected from optic fibers, sensors, micromachines, and combinations thereof.

5. A process for measuring and monitoring electrical motor systems, said process comprising:

providing a motor system having at least one motor component selected from a stator and an armature, said at least one component connected to at least one electrical wire;

providing at least one means for data measurement;

connecting said at least one means for data measurement with said at least one motor component;

collecting data with said at least one means for data measurement; and

transferring said collected data to a data collection station.

5 6. A process according to claim 5 wherein said means for collecting data is contained within a tube.

7. A process according to any preceding claim wherein the motor is an electrical motor of a downhole electrical submersible pump for pumping of hydrocarbon fluids in a well.

10 8. A system for use in claim 4 which comprises a fibre optical cable provided with physical parameter sensors embedded in an electrical insulation coating surrounding at least one wire of the motor windings.

1/1

Fig.1.





Fig.2.



Fig.3.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/02669

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H02K11/00 H02K3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H02K G01R H01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 295 03 853 U (ASTA ELEKTRODRAHT GMBH) 1 June 1995 (1995-06-01) the whole document	1-8
X	US 4 827 487 A (TWERDOCHLIB MICHAEL) 2 May 1989 (1989-05-02) column 3, line 27 -column 5, line 33; figures 1-5	1,5

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

7 August 2000

Date of mailing of the international search report

17/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3018

Authorized officer

Hijazi, A

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/02669

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 29503853 U	01-06-1995	AT 1161 U	25-11-1996
		DE 19507941 A	14-09-1995
		IT MI950465 A	11-09-1995
US 4827487 A	02-05-1989	NONE	